

CX-EPD1289L Surface Mount Preload RIM Strike



CX-EPD1289L

CX-EPD1289L-BK

Camden introduces the first surface mount RIM strike with preload in the security industry. The CX-EPD1289L grade 1 surface mount RIM strike, with latch monitoring, also offers a 'Universal' strike design that delivers unparalleled application flexibility, with both UL security and fire listings.

Preload is pressure exerted on the keeper of a strike that causes the mechanism to fail to release. Whether caused by air pressure, a misaligned door, or inexact installation, CX-EPD1289L RIM strikes are designed to operate where other strikes fail!

This award-winning strike is now available in a unique all-black finish, including the jaws and latch monitor.



EXCLUSIVE
PRODUCTS







BEST QUALITY

Features

- 'No Cut' surface mount RIM strike for Pullman latches
- Operates with up to 15 lbs. of preload pressure
 - US Patent: 10988959
- 'Universal' design with selectable:
 - 12/24V, AC/DC operation
 - Fail Safe/Fail Secure operation
- 3/4" latch projection
- Latches operate independently of each other
- Metal mounting jig included for easy installation
- Available in stainless steel and unique all-black finish
- Heavy duty stainless steel construction
- Horizontal adjustment, spacer plate available
- Removable latch monitoring switch included
- Non-handed, left or right
- 5 year warranty



SPECIFICATIONS		DIMENSIONS	
Latch Projection:	3/4"	CX-EPD1289L  Top	CX-RIM-SB  Top
Voltage:	12/24V AC/DC		
Current Draw:	560mA @12V DC 280mA @24V DC	 Side Front	 Side Front
Static Strength:	1,500 lbs. (UL Verified)		
Dynamic Strength:	70 ft-lbs.		
Preload:	15 lbs.		
Endurance:	1,000,000 Cycles (Factory Tested) 250,000 Cycles (UL Verified)		
Fire Rating:	UL10C/CAN4-S104 3hrs. (Fail Secure Mode Only)		
Mode:	Field Selectable Fail Safe or Fail Secure		
Operation:	AC Buzz, DC Silent		
Duty:	Continuous		
Latch Monitor:	SPDT, 100mA @ 24V DC, Resistive		
Dimensions:	CX-EPD1289L: 9-3/16"H x 1-15/16"W x 3/4"D (233mm x 49mm x 20mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)		

ORDERING INFORMATION	
MODELS	
CX-EPD1289L	Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, c/w 'plug-in' latch monitor assembly and metal mounting jig.
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, c/w 'plug-in' latch monitor assembly and metal mounting jig.
SPACER PLATE	
CX-EPD1289-SPC	Spacer plate for CX-EPD1289L surface mount RIM strike
SURFACE MOUNTING BOX	
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door