

LOCKING PRODUCTS

CX-EPD1289L SERIES: 3/4" SURFACE MOUNT FIRE RATED RIM STRIKES WITH PRELOAD

UL10C/ US CAN4-S104,











CX-EPD1289L Series 3/4" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. These award-winning strikes are now also available in a unique all-black finish, including the jaws and latch monitor.

Features

- Up to 15 lbs. of preload pressure
- 3/4" latch projection
- · 'Plug-in' latch bolt monitor included
- · 'No-cut' surface mount
- · Metal mounting jig included
- · Tamper resistant stainless steel construction
- · Non-handed, with plug-in wiring harness
- · Stainless steel cover plate included
- · 5 year warranty

MODELS		List Price
CX-EPD1289L	3/4" Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$550.00
CX-EPD1289L-BK	All-black finish, surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe / fail secure, w/ 'plug-in' latch monitor assembly and metal mounting jig	\$600.00
SPACER PLATE List Pri		List Price
CX-EPD1289-SPC	1/8" Spacer plate for CX-EPD1289L surface mount RIM strike	\$20.00
SURFACE MOUNTING BOX List Price		
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$55.00

Specifications

Voltage:	12/24V, AC/DC		
Current Draw:	560mA @ 12 VDC 280mA @ 24 VDC		
Strength - Static: 1,500 lbs. Dynamic: 70 Ft- lbs.			
Preload (Fail-Secure Only): 15 lbs.			
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)		
Mode: Fail-safe / Fail-secure Duty: Continuous			
Fire Rating: UL10C/CAN4-S104 3 hrs. (Fail Secure)			
Mechanical Adjustment: Strike Body			
Operation:	AC-Buzz, DC-Silent		
Latch Projection: 3/4"			
Latch Bolt Monitor: SPDT, 100mA @ 24 VDC			
Dimensions:	CX-EPD1289L: 9-3/16"H x 1-15/16"W x 3/4"D		

9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)

(233mm x 49mm x 20mm)

CX-RIM-SB:



CX-EPD1289-SPC