



CX-EPD1299L SERIES: 1/2" SURFACE MOUNT RIM STRIKES WITH PRELOAD

CX-EPD1299L Series 1/2" Grade 1 electric RIM strikes for pullman latches offer the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959.



UL 1034
UL 294



Features

- 'Universal' design, UL Security Listed
- 1/2" latch projection
- 2 Spacer plates included: 1/8" and 1/4"
- Stainless steel or all-black finish
- Up to 15 lbs. of preload pressure on strike keepers
- Plug-in latch bolt monitor assembly included
- 5 year warranty

MODELS

		List Price
CX-EPD1299L	1/2" Surface mount Grade 1 RIM, brushed aluminum finish strike with preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$575.00
CX-EPD1299L-BK	1/2" Surface mount Grade 1 RIM strike, all-black finish, w/ preload, 12/24V, AC/DC, fail safe/fail secure, w/ 'plug-in' latch monitor assembly & metal mounting jig	\$625.00
SURFACE MOUNTING BOX		List Price
CX-RIM-SB	Aluminum surface mounted adapter box for mounting EPD-1289L (or 1299L) on a double door	\$55.00

Specifications

Voltage:	12/24V, AC/DC
Current Draw:	560mA @ 12VDC 280mA @ 24VDC
Strength - Static:	1,500 lbs. Dynamic: 70 Ft- lbs.
Preload (Fail-Secure Only):	15 Lbs.
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)
Mode:	Fail-safe / Fail-secure Duty: Continuous
Mechanical Adjustment:	Strike Body
Operation:	AC - Buzz, DC - Silent
Latch Projection:	1/2"
Latch Bolt Monitor:	SPDT, 100mA @ 24 VDC
Dimensions:	CX-EPD1299L: 9-3/16"H x 1-15/16"W x 9/16" D (233mm x 49mm x 14mm) CX-RIM-SB: 9-3/16"H x 1-31/32"W x 1-1/4"D (233mm x 50mm x 32mm)



CX-RIM-SB